CELESTION

Coaxial Loudspeakers

TFX0615








- · Silk dome tweeter
- · Integrated HF waveguide
- 110° nominal HF coverage

Frequency Response and Impedance Curves



Black: LF response curve | Red: HF response curve

Power rating: Tested for two hours using a continuous, band-limited pink noise signal as per AES standard. Power calculated on minimum impedance Loudspeaker tested in free air.

HF power rating: Tested for two hours on plane wave tube using a continuous, band-limited pink noise signal as per AES standard. Power calculated on minimum impedance.

Continuous power rating: Defined as 3dB greater than the AES rating.

Sensitivity: Measured on axis at 1W, 1m in 2 anechoic environment.

Xmax: 0.5*(Hvc-Hg) + 0.25*Hg

Suggested crossover design available online at celestion.com/speakerworld

General Specifications

Nominal Diameter 165mm / 6.5in 150W Power Rating Continuous power rating 300W Rated impedance 8 94dB Sensitivity Frequency range 100-6000Hz Chassis type Pressed steel Magnet type Ferrite Magnet weight 0.81kg / 23oz Voice coil diameter 38mm / 1.5in Voice coil material Round copper Former material Polyimide Cone material Kevlar loaded paper

Surround material Cloth-sealed Suspension Single Xmax 5.25mm / 0.21in Gap height (Hg) 6mm / 0.24in VC winding height (Hvc) 13.5mm / 0.53in

Mounting Information

 Overall diameter
 178mm / 7in

 Overall depth
 75.5mm / 3in

 Cut-out diameter
 145mm / 5.7in

 Mounting hole dimensions
 4mm / 0.16in

Number of mounting holes 4
Mounting hole PCD 4
168.5mm / 6.63in

Unit weight 4.6lb / 2.1kg

Parameters

Sd 153.94cm2 / 23.86in2

Fs 96.80Hz

Mms 12.62g / 0.45oz

Qms 3.038

Qes 0.429

Qts 0.376

Re 5.39

Vas 7.181 / 0.25ft3

 Vas
 7.18I / 0.25ft3

 Bi
 9.82Tm

 Cms
 0.21mm/N

 Rms
 2.53kg/s

 Le (at 1kHz)
 0.46mH

 Xmax
 5.25mm / 0.21in

Additional HF Specifications

Power rating 10W
Continuous power rating 20W
Rated impedance 8
Sensitivity 98dB

Frequency range 1700-20,000Hz
Recommended min. crossove 2200Hz

r 12dB/oct

Voice coil diameter 25mm / 1in
Magnet type Neodymium
Diaphragm material Silk
Surround material Silk

Packed Dimensions & Weight

Multi pack qty 36

Multi pack size W x D x H $\,$ 742mm x 541mm x 300mm / 29.2in

x 21.3in x 11.8in

Multi pack weight 80kg / 176lb



Celestion, Claydon Business Park, Great Blakenham, Ipswich, IP6 0NL United Kingdom